3L/CC GC









HONDA GC190

HONDA









APPLICATIONS



Domestic Cleaning





Motor Bike Cleaning



Light Agriculturist





STANDOUT FEATURES



OEM[™] sealed axial pump delivers performance with power boost.



Domestic reliable Honda™ GC190 pull start series engine.



thermal valve to prevent overheating in excessive bypass.



10" pneumatic tyres.



0°, 15, 25, 40 and soap **snap-on** nozzles.



Dual M22 screw hose coupling system.















TECHNICAL DATA 0:00	BLACK GC	
Product Code	CW3300-9.1P	
Pressure / Flow Rate	3300 PSI (230 BAR) / 9.1 L/PM (546 L/PH) / 2.4 GPM 60°C / 140°F	
Max Inlet Temp		
Class (AS/NZS: 4223)	A (2,093 Bar/Litres)	
Usage Frequency	Domestic: Occasionally O3	
Nozzle Size		
Frame Structure	Heavy duty steel black powder coat 2-wheel trolley	
MOTOR FEATURES 💍		
Engine / Power	Honda [™] GC190 Pull Start (air cooled) 6HP / 190cc	
Fuel Type / Capacity / Protection	Unleaded / 2L / Low Oil Shutdown	
HYDRAULIC FEATURES 🖑		
Pump / Head / Pistons	Axial (OEM) / Brass / Ceramic Coated	
Motor Pump Coupling / Pump RPM	Direct Drive / 3400RPM	
Unloader Valve	Intogral	

HYDRAULIC FEATURES	~ ~	
Pump / Head / Pistons		Axial (OEM) / Brass / Cerami

Unloader Valve Integral

Detergent Injector Yes - Downstream low pressure (with powerboost technology)

DIMENSIONS & WEIGHT

Machine Dimensions / Weight $800mm(L) \times 520mm(W) \times 580mm(H) / 36KG$

WARRANTY(S) 🕢

Unit / Pump Warranty* 1 Year (Domestic Use Only) Engine Warranty* 2 Years (Domestic Use Only)

OPTIONAL ACCESSORIES

10m Extension Hose + M22 Joiner JWA018-EX JW3 Foaming Lance with Tank JWA221 12" Hammerhead with Lance JWA-FSC15-CMPL

Copyright © 2023 Jetwave® Group Pty Ltd. All Rights Reserved.

The manufacturer reserves the right to modify design features and technical facts without notice; due to our principals of continuous improvement.

*Coverage against defects in material and workmanship (refer to Jetwave's and component partners T&Cs).

V3.0 08/23

