

Wet Cleaning Only





## STANDOUT FEATURES



2 x double stage motor with by-pass cooling.

Independent motors with ON/OFF



noise levels.

Professional submerged pump allows holding tank to be automatically emptied during operation via float

Sound absorbent filter to ensure low



Ultra shock proof plastic holding tank & UV and shock resistant plastic head.



Powerhook<sup>™</sup> 2-stage strong flexible nylon core cleat for easy remove of head.



illuminated switches.

## STANDARD EQUIPMENT

2.5m Flexible hose with connection ø38mm 2 x plastic tubes ø38mm



Wet Floor tool ø38mm



TECHNICAL DATA 0:00	DACOTA 429 SUB & SLURRY (FUMP OUT)
Product Code	10304/2/50
Intended Application	Wet Only
Cable Length	8.5m
Air Flow	420m <sup>3</sup> /h
Water Flow	180l/pm
Water-lift	2470mmH <sup>2</sup> 0
Tank Capacity	90L
Material	Plastic (Polyethylene)
Diameter of Accessories	ø38mm
Standard Hose Length	2.5m
Sound Pressure Level	74dB
PUMP FEATURES 🕌	
Pump Type	Plastic
Pump Power	370 watts
Pump Capacity	1801/pm
Delivery Head	7m
MOTOR FEATURES	
Power / Voltage	2400 Watts / 240v
Motor(s) / Stage	2 / 2
DIMENSIONS & WEIGHT 🇊	
Vacuum Dimensions / Weight	450mm(L) x 500mm(W) x 950mm(H) / 26KG
WARRANTY(S) 🕢	
Vacuum	T Year(s)
OPTIONAL CONSUMABLES	
NYLON BAG (700 MICRON)	FTDP00559
OPTIONAL ACCESSORIES	
ADDITIONAL Ø38MM FLEXIBLE HOSE	50200

The manufacturer reserves the right to modify design features and technical facts without notice; due to our principals of continuous improvement. \*Coverage against defects in material and workmanship (refer to Jetwave's and component partners T&Cs).

🌻 10-16 Smith Street, Thebarton, 5031, South Australia, AU 🛛 🌜 +61 8 8371 3599 🛛 🔀 sales@jetwave.com.au 🛛 🚎 jetwavegroup.com

V2.2 08/21