EXPLORER ©2D 210-15









KOHLER KD15-440 DIESEL

KOHLER. Diesel





HERO INNOVATIONS



Top Lifting Lugs



PEXO™

Stainless Steel Exoskeleton



JWPP™

Jetwave UDOR™ Italian Premium Pump



CC™

Centralised Control



AVPS™

Anti Vibration Protection System



Multi Configuration





Registered Design ® 202215869

APPLICATIONS



Tradesmen




Construction/Earth Moving



Mine Sites



Hire & Rental





STANDOUT FEATURES



JW® UDOR® Premium Italian plunger pump running at 1450RPM, delivers more performance and longer life.



Industrial Kohler[™] KD15-440 series air cooled engine, with cyclonic air pre filter and twin fuel filtration for increased reliability.



Jetwave Safety System™ (JSS) thermal and safety valve to prevent overheating in excessive bypass and over pressurisation.



Zero line pressure brass adjustable unloader valve.



Vertical burner with GeniSys™ 12v Advanced Burner Control with smart sensors and protective features.



Battery isolator & Emergency stop for increased safety and longevity.









STANDARD EQUIPMENT





Gun: J5500k low trigger force gun w/swivel & lance coupling system.

Lance: JW Straight stainless steel lance w/ snap coupling + nozzle w/protector & tail





Hose: 15m non marking double wire braid

hose w/M22 couplings

Chemical: JW easy foam kit w/1L bottle







DIMENSIONS (MM)

TECHNICAL DATA 0:00

EXPLORER 62D 210-15

Product Code HW3000-15DG2

Pressure / Flow Rate 3150 (210 BAR) / 15 L/PM (900 L/PH) / 4 GPM

Max Water Inlet / Outlet Temp 60°C / 90°C

Class (AS/NZS: 4223) A (3,150 Bar/Litres)

Usage Frequency Professional: Daily Usage

Nozzle Size 045

Frame Structure CNC Modular skid galvanised steel chassis plus satin powder coat finish and stainless steel cover

MOTOR FEATURES



Kohler™ KD15-440 Electric Key Start (air cooled) 10HP / 441cc

Fuel Type / Capacity / Protection Diesel / 3.4L / Low Oil Shutdown

HYDRAULIC FEATURES

Pump / Head / Pistons

JW® UDOR® Premium Triplex Plunger / Brass (Nickle Plated) / Ceramic

Motor Pump Coupling / Pump RPM

Gearbox Drive / 1450RPM

Unloader Valve Independent (Zero) - Adjustable

Safety Valve Yes

THERMAL FEATURES

Burner Model Vertical 12v V Series

Diesel / 20L / 5.74 L/PH Fuel Supply / Capacity / Consumption

Mild steel 3mm wall seamless (400BAR rated) / Stainless Steel Coil / Housing Material

DIMENSIONS & WEIGHT



Machine Dimensions / Weight

1100mm(L) x 700mm(W) x 920mm(H) / 280KG (approx.)

WARRANTY(S) 🕢

Unit / Pump Warranty*

2 Years

KOHLER, Diesel Engine Warranty* 3 Years

OPTIONAL ACCESSORIES

OPTIONAL UPGRADES

30m Hose Reel w/30m of hose	1060CMPL-EXPD30M	Engine Hour Metre	ACD-TACHO
60m Hose Reel w/60m of hose	1067CMPL EXPD60M	4 Wheel Trolley Kit A (4xOffroad Wheels)	JWA407
JW Bypass Pro Foam	PROFOAM	4 Wheel Trolley Kit B (2xCastor Wheels 2xOffroad Wheels)	JWA407E
JW Pro Turbo Head	JWA1303.045	Hose Reel Roller Guide HGS™	1067-GUIDEASSY
21" Hammerhead - ABS Plastic	JWA-FSC21	Mine Specification Kit	G2DMINESPEC-B
21" Hammerhead - Stainless Steel	JWA-FSC21-5		

Copyright © 2023 Jetwave® Group Pty Ltd. All Rights Reserved.

The manufacturer reserves the right to modify design features and technical facts without notice; due to our principals of continuous improvement.

*Coverage against defects in material and workmanship (refer to Jetwave's and component partners T&Cs).

V3.0 08/23



