



CLASS A AS/NZS 4233.1
PRESSURE CLEANER
NO RTO CERTIFICATION REQUIRED FOR OPERATORS

JETWAVE®

HIGH PRESSURE CLEANERS

SENATOR™ G2 4000 psi • 20 l/pm



Petrol Driven



Cold Water



Daily Usage

FIELDS OF APPLICATION

Roof Cleaning
Painting Contractors
Cleaning Contractors
Boat Yards and Ports
Agricultural Equipment
Councils & Government



JETWAVE
POWERED BY
HONDA



NEW

The Jetwave® Senator™ G2 revolutionises the twin cylinder gearbox petrol driven high pressure cold water pressure cleaner powered by HONDA™. Australian engineered and assembled; its innovation provides heavy duty users with a compact powerful, safe and easy to use unit that encompasses stainless steel exoskeleton (PEXO™) cover protection, centralised control & multi-configurable design.



HERO INNOVATIONS



Stainless Steel Exoskeleton (PEXO™)

Protective formed CNC cover to safeguard all components and for increased safety.



Multi Configuration

Industry first customisable modular build with precision heavy gauge steel chassis. Build it your way.



Centralised Control

Easily accessible one panel fascia mounted control(s) & components.



AVPS™

Anti-vibration protection system (AVPS™) for quieter & reliable performance.



Convenient

Tie down points and forklift tyne pockets for on-site lifting ability.



Versatile

Multiple hose reel configurations.

STANDOUT FEATURES



JW® Enhanced Italian triplex plunger pump delivers performance and longer life.



Low speed professional pump for increased reliability and longer maintenance intervals.



Electric Start HONDA™ V-TWIN GX630 industrial series engine.



Dual M22 screw hose quick coupling system.



Heavy duty washable inlet water filter.



Battery isolator.



Digital hour meter.



Jetwave Safety System™ (JSS) thermal & safety valve to prevent overheating in excessive bypass and over pressurisation.



Integrated accessory storage for gun and lance.



Professional line accessories.



Stainless Steel pressure gauge.



Brass unloader valve.



Emergency Stop.



Forklift pockets.



Jetwave Group
 10-16 Smith Street Thebarton |
 Adelaide | South Australia | 5031 | AU
 +61 8 8371 3599
 sales@jetwave.com.au
 jetwave.com.au

Protection - Designed for durability and a long life.

Quality - JW Premium Industry proven 'Italian' pump.

Robust - Precision CNC frame.

Power - Easy start HONDA™ GX630 engine.

Flexibility - Multi configurable compact frame.



STANDARD EQUIPMENT



J5000™ Gun - with M22 swivel and extension.

Lance / Nozzle - Dual lance with variable pressure control complete with hardened nozzles.

Hose - 15m of 3/8" double wire braided hose with quick coupling(s).

OPTIONAL ACCESSORIES

Accessory	p/n	Included
High Pressure Swivel	p/n	Included
Additional High Pressure Hose (per metre)	p/n	52001
Complete Turbo Head with Lance	p/n	JWA160
JW12 Foaming Lance with Tank	p/n	JWA221-LS12
JW Pro Foam Bypass System	p/n	PROFOAM.05
OEM Hose Reel (30m Capacity)	p/n	1060CMPL
Pro Rapid Style Hose Reel (60m Capacity)	p/n	1067CMPL
Pro Rapid Stainless Steel Hose Reel (60m Capacity)	p/n	1067CMLSS
Hammerhead™ FSC 21" ABS - Plastic	p/n	JWA-FSC21.05
Hammerhead™ FSC 21" Stainless Steel	p/n	JWA-FSC22.05
Giraffe™ Alloy Telescopic Lance	p/n	JWA-TELE7.3.05
Sandblasting Kit	p/n	JWA164
Sludge Kit	p/n	80005
15m Drain Cleaning Whip Hose	p/n	HOP2X15VF
Professional Drain Cleaning Kit	p/n	JWA-PDCK
Vulcan V1 Hot Box	p/n	10199

OPTIONAL MACHINE UPGRADES

Upgrade	p/n	Included
Digital Engine Hour Meter, Emergency Stop, Battery Isolator, Forklift Pockets, 4 Wheel Trolley Kit	p/n	Included
HONDA™ iGX700 Fuel Injected	p/n	JWA-FI2
On-board 40L Water feed/Bypass tank	p/n	90008-40G2
Low level Water Cut Out	p/n	JWA220
Flat Bed Mounting Kit	p/n	JWA602
Double Stacked Front Hose Reel Plate Kit	p/n	JWA429
Van Mount Drip Tray	p/n	JWA432

Product Code	p/n	CW4000-20PEG2
--------------	-----	---------------

TECHNICAL DATA

Working Pressure	psi / bar	4000 / 275
Flow Rate	l/pm	20
Max Water Inlet Temp	°c	60

INTENDED APPLICATION

Usage Frequency	hours / type	4 - 6 Daily / Daily Usage
Category of Dirt / Debris	type	Medium - Heavy
Class (AS/NZS: 4233)	grade	A (5,500 BAR/LITRES)

MOTOR FEATURES

Engine	type	HONDA™ GX630 (4 stroke, air cooled)
Power	cc	630
Fuel Supply	type	Unleaded
Fuel Capacity	litres	27
Low Oil Shutdown	y / n	Y
Hour Meter	y / n	Y
Starting System	type	Electric Key start

HYDRAULIC FEATURES

Pump / Head / Pistons	type	JW® Italian Triplex Plunger/Brass (Nickel Plated)/Ceramic
Motor Pump Coupling	type	Gearbox Drive
Pump Speed	rpm	1450
Unloader Valve	type	Independent
Safety Valve	y / n	Y
Orifice / Nozzle	size	05

OTHER FEATURES

Adjustable Pressure	y / n	Y
Hose Reel Provision	y / n	Y (3 positions)
Frame Structure	type	CNC Modular skid with heavy gauge galvanised steel chassis plus safin powder coat finish and stainless steel cover
Onboard Accessory Storage	y / n	Y
Detergent Injector	y / n	Y - Downstream low pressure adjustable

DIMENSIONS & WEIGHT

Approx Weight	kg	180 unit / 195 boxed
Unit Dimensions	mm	910(L) x 670(W) x 1000(H)
Boxed Dimensions	mm	1200(L) x 800(W) x 1200(H)
Number per Pallet	type: pieces	Euro: 1

WARRANTY(S)

Engine Warranty*	year(s)	3 
Pump Warranty*	year(s)	2 

*Coverage against defects in material and workmanship (refer to Jetwave's and component partners T&Cs). The manufacturer reserves the right to modify design features and technical facts without notice; due to our principals of continuous improvement.